

**Declaration of performance (EN)**  
**No. DoP-106-BG**


VI



**GRASPOINTNER**  
Sustainable innovation.



**FILCOTEN**  
a brand of BG

1. Unique identification code of the product-type:	drainage channels out of concret - FILCOTEN HPC (High Performance Concrete) - for vehicular and pedestrian areas according to standard EN 1433													
2. Type, batch or serial number required pursuant to Article 11(4): <b>channel-type:</b> FILCOTEN pro NW 100: FILCOTEN pro NW 150: FILCOTEN pro NW 200: FILCOTEN pro NW 300:	<b>FILCOTEN pro, pro mini</b> Type M, cl. E 600 kN (edge out of galvanised steel or stainless steel)  <u>articlenumbers according to currently valid brochure/price list:</u> I05102.., I05103.., I06102.., I06103.. I05152.., I05153.., I06152.., I06153.. I05202.., I05203.., I06202.., I06203.. I05302.., I06302..													
3. Intended use as foreseen by the manufacturer:	drainage channels for vehicular and pedestrian areas													
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):	BG-Graspointner GmbH Gessenschwandt 39, A-4882 Oberwang Telefon: +43 (0) 6233 / 8900-0 / Fax: +43 (0) 6233 / 8900-303 E-Mail: office@graspointner.at													
5. Name and contact address of the authorised representative specified in Article 12(2):	not applicable													
6. System as set out in annex V:	system 3													
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:	The notified body, Staatlich akkreditierte OÖ. Boden- und Baustoffprüfstelle GmbH Schirmerstraße 12, A-4060 Leonding (No. 1661 according to building products guideline) based on type testings for drainage channels on the basis of solid BG-Graspointner samples, has determined compliance with the requirements specified by the standard.													
8. Declared performance:	<table border="1"> <thead> <tr> <th>essential characteristics</th><th>performance</th><th>harmonised technical specification</th></tr> </thead> <tbody> <tr> <td>Water tightness (connection of elements)</td><td>fulfilled</td><td rowspan="4">EN 1433:2006</td></tr> <tr> <td>Load capacity</td><td>fulfilled</td></tr> <tr> <td>Deformation under load</td><td>NPD</td></tr> <tr> <td>durability</td><td>W +R</td></tr> </tbody> </table>		essential characteristics	performance	harmonised technical specification	Water tightness (connection of elements)	fulfilled	EN 1433:2006	Load capacity	fulfilled	Deformation under load	NPD	durability	W +R
essential characteristics	performance	harmonised technical specification												
Water tightness (connection of elements)	fulfilled	EN 1433:2006												
Load capacity	fulfilled													
Deformation under load	NPD													
durability	W +R													
9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4:	Signed for and on behalf of the manufacturer by:  Oberwang, 01.02.2019 (place and date of issue)	 Bernhard Knoblechner, GF (name and function)												